


Some results and reflections:

# Water quality during reduced occupancy due to COVID-19 and select intervention methods

Andrew J. Whelton, Ph.D.


Caitlin Proctor, Ph.D., Christian Ley, Kyungyeon Ra, Danielle Angert, Elizabeth Montagnino, Yoorae Noh, Maria Palmegiani, Ryan Day, Andrew Golden











# Some of our efforts involved testing building water systems in response to the pandemic

11 buildings across 4 studies All free chlorine disinfectant 3-5 months of low/no water use Some served by the same utility Some have recirculation loops, inbuilding storage, showers All had indoor copper pipe Up to 400 water outlets/building Not all had as-built drawings



- 1. Elementary school, Indiana (Ra et al.)
- Large residential building, Indiana (Angert et al., led by Proctor, Ph.D.)
- 3. Institutional buildings, Indiana (Ra et al.)
- 4. Elem/mid/high school, Ohio (Ley et al.)




### In Ohio, a utility and an 8 year old LEED K-12 school reached out for assistance.

- Utilities across the U.S. saw increased residential demand (+43%) and reductions in commercial (-46%) and industrial (-21%) demands (Faust et al. 2021)
- 1 water utility found that after 6 months of low water use, free chlorine levels were not detectable after the school building had been flushed
- We setout to examine water quality in the 2 story building
  - No water management program or flushing plan
  - 220 sinks, 31 water fountains, 30 showers, and 1 hydrotherapy spa in the facility's athletic training room.
  - Water heating set at 140° F (60° C). 2 boilers with a 500 gallon hot water storage tank. No recirculation system.
  - Rainwater used for toilet flushing NOT potable water –

Ley et al. (In preparation)



The school had a >95% reduction in water use during the shutdown



Ley et al. (In preparation)




## Metal levels were not consistent across the school, were impacted by flushing, and the 8 year old hot water system was excessively corroding

Some Cu levels exceeded the acute health-based limit of 1,300  $\mu$ g/L, while others did not

Zn exceeded the USEPA health advisory level at 1 cafeteria soup filling station because of nonuse and stainless steel piping

Nonpotable fixtures used for potable purposes

**Hot water system** had excessive corrosion. Discolored water was observed





Ley et al. (In preparation)



Legionella was detected before and immediately after the shock disinfection + flushing intervention

Sample type	Fixture type	<i>L. Pneumophila</i> conc., MPN/100 mL	Exceeded suggested <i>L. pneumophila</i> Limit, 106 CFU/mL
Initial stagnation	Water fountain	239.6	Yes
	Staff sink (cold)	1,289.6	Yes
	Cafeteria sink (cold)	3.5	No
	Cold faucet (distal end)	1	No
	Cold faucet (central)	1.1	No
Pre-shock chlorination	Various	0	No
Immediately after shock	Various	0	No
	Fountain Bathroom sink	<u>3.9</u> <u>7.9</u>	No No
72 hr post-shock	Various	0	-
1 mo. post-shock	Various	0	-

#### **Stagnation:**

5.3% (n=5 of 94 total) of sampled fixtures tested positive for *L. pneumophila*.

#### After shock:


L. pneumophila was detected in 2 fixtures (drinking water fountain, sink thermostatic mixed valve)

#### One month after shock:

L. pneumophila not detected1 month after the shockdisinfection



### TTHM and copper levels were affected by the shock disinfection and flushing procedure



TTHM levels in plumbing >> water utility's distribution system

Highest TTHM levels: Shock chlorination (mean: 135.3 μg/L).

Highest number of exceedances: 72 hours after the shock + flushing, 7 / 15 samples


Some samples had copper levels exceed 1.3 mg/L post-shock, while lead was unaffected.

Hypochlorite shock disinfection levels varied 160-340 mg/L+


Ley et al. (In preparation)



### An Indiana School: 3 buildings and a 3 month shutdown







- Little to no chlorine found at stagnant fixtures
- Ni exceeded the health based limit in 3 month stagnant water before flushing, but other metals were okay. Cu did not exceed safe limits. Pb found at a maximum of 3.5 ug/L.
- *L. pneumophila* detected in all buildings, but not at all locations (1.1 to 188 MPN/100mL): bathroom sinks, class sinks, water fountains.
- After complete building flushing and 2 weeks later, the pathogen was not detected.

Ra et al. (In preparation)



### The pandemic put a spotlight on plumbing safety...



























































OF MINNESOTA

















Lucerne University of Applied Sciences and Arts

health officials, industry, governments, institutions, and more responded.



## To Address the Public Health Knowledge Gap Building Water Essentials – Public Health 10 Hour, Online Short-Course



Input from practicing engineers, scientists, utilities and public health officials.



A training tool, an encyclopedia, and an extensive FAQ, designed to be immediately applicable in the field.



Modules do not have to be taken in sequence.





If interested e-mail <a href="mailto:EngrOnline@purdue.edu">EngrOnline@purdue.edu</a>
Info and registration: <a href="https://cutt.ly/Sg4RXJv">https://cutt.ly/Sg4RXJv</a>








#### Plumbing Safety <u>Decision Support Tool</u> Coming Soon:

Right Sizing Tomorrow's Water Systems for Efficiency, Sustainability, and Public Health, 2016-2021

Supported by a grant from:











Andrew Whelton, Jade Mitchell, Joan Rose, Juneseok Lee, Pouyan Nejadhashemi, Erin Dreelin, Tiong Gim Aw, Amisha Shah, Matt Syal, Maryam Salehi












### Thank you.

### Andrew Whelton, Ph.D. <u>awhelton@purdue.edu</u> @TheWheltonGroup



- ✓ Online short-course
- ✓ Plumbing education videos
- ✓ Flushing plans
- ✓ Plumbing explainers
- ✓ List of projects
- ✓ Scientific opinions
- ✓ Resources → presentations
- ✓ Scientific reports
- External plumbing docs
- ✓ YouTube Channel

10 hr, 1 CEU, Self-paced, Online Building Water Essentials Short-Course:

https://engineering.purdue.edu/online/certifications/building-water-essentials

### www.PlumbingSafety.org

