

sp3c

The Extended Standard Product 3 Orbit Format (SP3-c)

(17 August 2010)

Steve Hilla
National Geodetic Survey
National Ocean Service, NOAA
Silver Spring, MD 20910-6233, USA

INTRODUCTION

The original Standard Product 3 format (SP3-a) was proposed in (Remondi, 1989) and modified and adopted in (Remondi, 1991). The SP3 format is similar to the original NGS Standard Product 1 format described in (Remondi, 1989 and 1985) but includes additional information: satellite clock corrections, orbit accuracy exponents, comment lines, the GPS week and seconds of week associated with the first epoch, and a more flexible header structure (Spofford and Remondi, 1994).

In 1998, W. Gurtner and M. Rothacher defined an SP3-b format to allow for the combination of GPS orbits and GLONASS orbits (see IGEX Mail 0042, 27-Oct-1998). All of these SP3-b modifications were backwards compatible with SP3-a, with the exception of the satellite identification labels -- which were changed from an I3 field to an A1,I2 field to accommodate both GPS and GLONASS identifiers in a manner similar to RINEX files (Gurtner, 2000).

At the 2000 International GPS Service (IGS) Analysis Center Workshop held at the U.S. Naval Observatory, it was suggested to modify the SP3 format still further so that orbit files distributed by the IGS could include some type of clock accuracy information, and so that separate accuracy information would be available for the observed versus predicted parts of the IGS ultra-rapid orbit files. Rather than just putting two sets of accuracy exponents in the header (one for the observed part and one for the predicted part) it was decided instead to put accuracy information at each epoch (for X, Y, Z, and satellite clock correction). Since the original SP3-a and SP3-b formats were only 60 columns wide, this additional information was easily added using columns 61 through 80 in each Position and Clock Record. This was done in such a way as to remain mostly backwards compatible with SP3-a. As comments were collected from the IGS (orbit) Analysis Centers, additional ideas emerged. It was suggested that a clock event flag be added in column 75 (as currently done by some groups) to denote events like a clock swap on a satellite. It was also suggested to add an orbit event flag, to denote cases where it was known that a satellite went through some type of orbit maneuver. It was also suggested that clock prediction and orbit prediction flags be added. Finally, for the purposes of computing user range errors more accurately for each satellite, it was suggested to add correlation information between the satellite coordinates and the satellite clock correction. These ideas were discussed further at the 2002 IGS Network, Data, and Analysis Center Workshop held in Ottawa (Hilla, 2002).

All of these suggestions have been incorporated in this new SP3-c format. As a result, there can now be as many as three different sets of satellite position accuracy indicators in an SP3-c file. The first set, the original accuracy exponents in the header, have been kept in SP3-c to maintain backwards compatibility with the SP3-a format and with existing GPS processing software. These exponents are interpreted as 2**nn millimeters. A zero exponent means the accuracy is unknown. The quoted orbit error should represent one standard deviation and be based on the orbital error in the

sp3c

entire file for the respective satellite. The second set, in columns 62 through 69 of the Position and Clock Record, represent the standard deviation of each position component (X, Y, and Z) at that epoch, in millimeters. These are also exponents but use a floating-point base (for example, 1.25**nn) to achieve better resolution for the standard deviations. A zero exponent here represents a 1 millimeter standard deviation. Blank spaces mean the standard deviation is unknown. These first two sets of standard deviations are expected to be present in all SP3-c files.

A third set of standard deviations can be found in the optional Position and Clock Correlation Record (the EP record). This optional record was added to provide high precision users with the correlation coefficients between the X, Y, Z, and satellite clock correction values. In order to be able to construct the full 4-by-4 covariance matrix for a satellite at an epoch, without any loss of precision, the standard deviations for the X, Y, and Z position components are given here to full millimeter precision using a range of 1 to 9999 millimeters. Blank spaces mean a standard deviation or a correlation coefficient is unknown (blanks would probably only occur for the clock information, unless the EP records were being used to store only standard deviations, or only correlation coefficients).

In this document the format fields for the SP3-c format are defined. These include all of the changes made for SP3-b. The fields that are defined as "blanks" are reserved fields which must remain blank. All times referred to in an SP3-c file are in the SAME time system, even when they are represented as Gregorian Dates or Modified Julian Dates. In SP3-c, the Time System code for the entire file (GPS, GLO, GAL, TAI, QZS, or UTC) is now specified in the header on line thirteen. The information to convert between GPS Time and Coordinated Universal Time (i.e., the leap seconds and the fractional error in GPS Time) is not provided as part of the SP3-c format. The basic format of an SP3 file is a Header, followed by a series of epoch times each with a set of Position and Clock Records listed for each satellite. A second, optional record contains satellite velocities and the clock correction rate-of-change. The Position Record Flag, P, in line one indicates that no velocities are included. The Velocity Record Flag, V, in line one indicates that at each epoch, for each satellite, an additional satellite velocity and clock rate-of-change has been computed. SP3-c adds two more optional records: a Position and Clock Correlation Record (EP record), and a Velocity and Clock Rate-of-Change Correlation Record (EV record).

Note: On 27 September 2006, this file was updated slightly to add more options for the Time System Indicator. The original version of this file, which was dated 5 September 2002, had only "GPS" and "UTC" as options for the Time System Indicator. This new version adds codes "GLO", "GAL", and "TAI". Also, clarifications were made regarding the EP and EV records, and the order of the satellites and records at each epoch.

Note: On 12 February 2007, this file was modified to include a reference to a new list of LEO satellites available at CDDIS (see the documentation below regarding the satellite identifiers found in the third through seventh lines).

Note: On 17 August 2010, this file was modified to add satellite system identifiers for J = QZSS and C = COMPASS, and to add "QZS" as a Time System indicator for QZSS Time.

Standard Product #3 ASCII SP3 Format Version "c".

Columns	Description	Example	Format
-----	-----	-----	-----

sp3c

SP3 First Line

Columns 1-2	Version Symbol	#c	A2
Column 3	Pos or Vel Flag	P or V	A1
Columns 4-7	Year Start	2001	I4
Column 8	Unused		blank
Columns 9-10	Month Start	__8	I2
Column 11	Unused		blank
Columns 12-13	Day of Month St	__8	I2
Column 14	Unused		blank
Columns 15-16	Hour Start	__0	I2
Column 17	Unused		blank
Columns 18-19	Minute Start	__0	I2
Column 20	Unused		blank
Columns 21-31	Second Start	__0.00000000	F11.8
Column 32	Unused		blank
Columns 33-39	Number of Epochs	____192	I7
Column 40	Unused		blank
Columns 41-45	Data Used	____d	A5
Column 46	Unused		blank
Columns 47-51	Coordinate Sys	__ITR97	A5
Column 52	Unused		blank
Columns 53-55	Orbit Type	__FIT	A3
Column 56	Unused		blank
Columns 57-60	Agency	__NGS	A4

SP3 Line Two

Columns 1-2	Symbols	##	A2
Column 3	Unused		blank
Columns 4-7	GPS Week	__1126	I4
Column 8	Unused		blank
Columns 9-23	Seconds of Week	__259200.00000000	F15.8
Column 24	Unused		blank
Columns 25-38	Epoch Interval	__900.00000000	F14.8
Column 39	Unused		blank
Columns 40-44	Mod Jul Day St	__52129	I5
Column 45	Unused		blank
Columns 46-60	Fractional Day	__0.00000000000000	F15.13

SP3 Line Three

Columns 1-2	Symbols	+_	A2
Column 3-4	Unused		2 blanks
Columns 5-6	Number of Sats	__26	I2
Column 7-9	Unused		3 blanks
Columns 10-12	Sat #1 Id	__G01	A1, I2.2
Column 13-15	Sat #2 Id	G02	A1, I2.2
	*		
	*		
	*		
Columns 58-60	Sat #17 Id	G21	A1, I2.2

SP3 Line Four

Columns 1-2	Symbols	+_	A2
Columns 3-9	Unused		7 blanks
Columns 10-12	Sat #18 Id	__G23	A1, I2.2

Columns 13-15	Sat #19 Id	sp3c G24	A1, I2.2
*			
*			
Columns 58-60	Sat #34 Id	__0	A1, I2.2

SP3 Line Five

Columns 1-2	Symbols	+-	A2
Columns 3-9	Unused	_____	7 blanks
Columns 10-12	Sat #35 Id	__0	A1, I2.2
Columns 13-15	Sat #36 Id	__0	A1, I2.2
*			
*			
*			
Columns 58-60	Sat #51 Id	__0	A1, I2.2

SP3 Line Six

Columns 1-2	Symbols	+-	A2
Columns 3-9	Unused	_____	7 blanks
Columns 10-12	Sat #52 Id	__0	A1, I2.2
Columns 13-15	Sat #53 Id	__0	A1, I2.2
*			
*			
*			
Columns 58-60	Sat #68 Id	__0	A1, I2.2

SP3 Line Seven

Columns 1-2	Symbols	+-	A2
Columns 3-9	Unused	_____	7 blanks
Columns 10-12	Sat #69 Id	__0	A1, I2.2
Columns 13-15	Sat #70 Id	__0	A1, I2.2
*			
*			
*			
Columns 58-60	Sat #85 Id	__0	A1, I2.2

SP3 Line Eight

Columns 1-2	Symbols	++	A2
Columns 3-9	Unused	_____	7 blanks
Columns 10-12	Sat #1 Accuracy	__7	I3
Columns 13-15	Sat #2 Accuracy	__8	I3
*			
*			
*			
Columns 58-60	Sat #17 Accuracy	__9	I3

SP3 Line Nine

Columns 1-2	Symbols	++	A2
Columns 3-9	Unused	_____	7 blanks
Columns 10-12	Sat #18 Accuracy	__9	I3
Columns 13-15	Sat #19 Accuracy	__8	I3
*			
*			

sp3c

*
Columns 58-60 Sat #34 Accuracy __0 I3

SP3 Line Ten

Columns 1-2 Symbols ++ A2
Columns 3-9 Unused _____ 7 blanks
Columns 10-12 Sat #35 Accuracy __0 I3
Columns 13-15 Sat #36 Accuracy __0 I3

*
*
*

Columns 58-60 Sat #51 Accuracy __0 I3

SP3 Line Eleven

Columns 1-2 Symbols ++ A2
Columns 3-9 Unused _____ 7 blanks
Columns 10-12 Sat #52 Accuracy __0 I3
Columns 13-15 Sat #53 Accuracy __0 I3

*
*
*

Columns 58-60 Sat #68 Accuracy __0 I3

SP3 Line Twelve

Columns 1-2 Symbols ++ A2
Columns 3-9 Unused _____ 7 blanks
Columns 10-12 Sat #69 Accuracy __0 I3
Columns 13-15 Sat #70 Accuracy __0 I3

*
*
*

Columns 58-60 Sat #85 Accuracy __0 I3

SP3 Line Thirteen

Columns 1-2 Symbols %c A2
Column 3 Unused _____ blank
Columns 4-5 File Type G_ A2
Column 6 Unused _____ blank
Columns 7-8 2 characters cc A2
Column 9 Unused _____ blank
Columns 10-12 Time System GPS A3
Column 13 Unused _____ blank
Columns 14-16 3 characters ccc A3
Column 17 Unused _____ blank
Columns 18-21 4 characters cccc A4
Column 22 Unused _____ blank
Columns 23-26 4 characters cccc A4
Column 27 Unused _____ blank
Columns 28-31 4 characters cccc A4
Column 32 Unused _____ blank
Columns 33-36 4 characters cccc A4
Column 37 Unused _____ blank
Columns 38-42 5 characters ccccc A5
Column 43 Unused _____ blank
Columns 44-48 5 characters ccccc A5

Column 49	Unused	sp3c	blank
Columns 50-54	5 characters	cccc	A5
Column 55	Unused		blank
Columns 56-60	5 characters	cccc	A5

SP3 Line Fourteen

Columns 1-2	Symbols	%c	A2
Column 3	Unused		blank
Columns 4-5	2 characters	cc	A2
Column 6	Unused		blank
Columns 7-8	2 characters	cc	A2
Column 9	Unused		blank
Columns 10-12	3 characters	ccc	A3
Column 13	Unused		blank
Columns 14-16	3 characters	ccc	A3
Column 17	Unused		blank
Columns 18-21	4 characters	cccc	A4
Column 22	Unused		blank
Columns 23-26	4 characters	cccc	A4
Column 27	Unused		blank
Columns 28-31	4 characters	cccc	A4
Column 32	Unused		blank
Columns 33-36	4 characters	cccc	A4
Column 37	Unused		blank
Columns 38-42	5 characters	ccccc	A5
Column 43	Unused		blank
Columns 44-48	5 characters	ccccc	A5
Column 49	Unused		blank
Columns 50-54	5 characters	cccc	A5
Column 55	Unused		blank
Columns 56-60	5 characters	ccccc	A5

SP3 Line Fifteen

Columns 1-2	Symbols	%f	A2
Column 3	Unused		blank
Columns 4-13	Base for Pos/Vel	1.2500000	F10.7
	(mm or 10** ⁻⁴ mm/sec)		
Column 14	Unused		blank
Columns 15-26	Base for Clk/Rate	1.025000000	F12.9
	(psec or 10** ⁻⁴ psec/sec)		
Column 27	Unused		blank
Columns 28-41	14-column float	0.000000000000	F14.11
Column 42	Unused		blank
Columns 43-60	18-column float	0.0000000000000000	F18.15

SP3 Line Sixteen

Columns 1-2	Symbols	%f	A2
Column 3	Unused		blank
Columns 4-13	10-column float	0.0000000	F10.7
Column 14	Unused		blank
Columns 15-26	12-column float	0.000000000	F12.9
Column 27	Unused		blank
Columns 28-41	14-column float	0.000000000000	F14.11
Column 42	Unused		blank
Columns 43-60	18-column float	0.0000000000000000	F18.15

sp3c

SP3 Lines Seventeen and Eighteen

Columns	Symbols	%i	A2
Column 3	Unused	—	blank
Columns 4-7	4-column int	— 0	I4
Column 8	Unused	—	blank
Columns 9-12	4-column int	— 0	I4
Column 13	Unused	—	blank
Columns 14-17	4-column int	— 0	I4
Column 18	Unused	—	blank
Columns 19-22	4-column int	— 0	I4
Column 23	Unused	—	blank
Columns 24-29	6-column int	— 0	I6
Column 30	Unused	—	blank
Columns 31-36	6-column int	— 0	I6
Column 37	Unused	—	blank
Columns 38-43	6-column int	— 0	I6
Column 44	Unused	—	blank
Columns 45-50	6-column int	— 0	I6
Column 51	Unused	—	blank
Columns 52-60	9-column int	— 0	I9

SP3 Lines Nineteen to Twenty two

Columns	Symbols	/*	A2
Column 3	Unused	—	blank
Columns 4-60	Comment	CC...CC	A57

SP3 Line Twenty three (The Epoch Header Record)

Columns	Symbols	*_	A2
Column 3	Unused	—	blank
Columns 4-7	Year Start	2001	I4
Column 8	Unused	—	blank
Columns 9-10	Month Start	— 8	I2
Column 11	Unused	—	blank
Columns 12-13	Day of Month St	— 8	I2
Column 14	Unused	—	blank
Columns 15-16	Hour Start	— 0	I2
Column 17	Unused	—	blank
Columns 18-19	Minute Start	— 0	I2
Column 20	Unused	—	blank
Columns 21-31	Second Start	— 0.00000000	F11.8

SP3 Line Twenty four (The Position and Clock Record)
(See example 1)

Column	Symbol	P	A1
Columns 2-4	Vehicle Id.	G01	A1, I2.2
Columns 5-18	x-coordinate(km)	— -11044.805800	F14.6
Columns 19-32	y-coordinate(km)	— -10475.672350	F14.6
Columns 33-46	z-coordinate(km)	— 21929.418200	F14.6
Columns 47-60	clock (microsec)	— 189.163300	F14.6
Column 61	Unused	—	blank
Columns 62-63	x-sdev (b**n mm)	— 18	I2
Column 64	Unused	—	blank
Columns 65-66	y-sdev (b**n mm)	— 18	I2
Column 67	Unused	—	blank
Columns 68-69	z-sdev (b**n mm)	— 18	I2

sp3c			
Column 70	Unused		blank
Columns 71-73	c-sdev (b**n psec)	<u>219</u>	I3
Column 74	Unused		blank
Column 75	Clock Event Flag	<u>E</u>	A1
Column 76	Clock Pred. Flag	<u>P</u>	A1
Columns 77-78	Unused		2 blanks
Column 79	Maneuver Flag	<u>M</u>	A1
Column 80	Orbit Pred. Flag	<u>P</u>	A1

If the user wishes to include correlation information between the position components and the clock correction, then an optional Position and Clock Correlation Record can be added after each Position and Clock Record. This record gives the standard deviations for X, Y, Z, and clock correction with greater resolution than the approximate values given in the Position and Clock Record.

SP3 Line Twenty five (The Position and Clock Correlation Record)
(See example 2)

Columns 1-2	Symbols	EP	A2
Columns 3-4	Unused		2 blanks
Columns 5-8	x-sdev (mm)	<u>55</u>	I4
Column 9	Unused		blank
Columns 10-13	y-sdev (mm)	<u>55</u>	I4
Column 14	Unused		blank
Columns 15-18	z-sdev (mm)	<u>55</u>	I4
Column 19	Unused		blank
Columns 20-26	clk-sdev (psec)	<u>222</u>	I7
Column 27	Unused		blank
Columns 28-35	xy-correlation	<u>1234567</u>	I8
Column 36	Unused		blank
Columns 37-44	xz-correlation	<u>1234567</u>	I8
Column 45	Unused		blank
Columns 46-53	xc-correlation	<u>5999999</u>	I8
Column 54	Unused		blank
Columns 55-62	yz-correlation	<u>-30</u>	I8
Column 63	Unused		blank
Columns 64-71	yc-correlation	<u>21</u>	I8
Column 72	Unused		blank
Columns 73-80	zc-correlation	<u>-1230000</u>	I8

The user can choose to include the optional Velocity and Clock Rate-of-Change Record, V, after each Position and Clock Record. The clock rate-of-change units are 10**-4 microseconds/second for cols. 47-60 below.

SP3 Line Twenty six (See example 2)

Column 1	Symbol	V	A1
Columns 2-4	Vehicle Id.	G01	A1, I2.2
Columns 5-18	x-velocity(dm/s)	<u>20298.880364</u>	F14.6
Columns 19-32	y-velocity(dm/s)	<u>-18462.044804</u>	F14.6
Columns 33-46	z-velocity(dm/s)	<u>1381.387685</u>	F14.6
Columns 47-60	clock rate-chg	<u>-4.534317</u>	F14.6
Column 61	Unused		blank
Columns 62-63	xvel-sdev (b**n 10**-4 mm/sec)	<u>14</u>	I2
Column 64	Unused		blank

		sp3c	
Columns 65-66	yvel-sdev	14	I2
	(b**n 10**-4 mm/sec)		
Column 67	Unused		blank
Columns 68-69	zvel-sdev	14	I2
	(b**n 10**-4 mm/sec)		
Column 70	Unused		blank
Columns 71-73	clkrate-sdev	191	I3
	(b**n 10**-4 psec/sec)		
Columns 74-80	Unused	_____	7 blanks

If the user wishes to include correlation information between the velocity components and the clock correction rate-of-change, then a separate Velocity and Clock Rate-of-Change Correlation Record can be added after each Velocity and Clock Rate-of-Change Record. This record gives the standard deviations for the X-, Y-, Z-velocities and the clock correction rate-of-change with greater resolution than the approximate values given in the Velocity and Clock Rate-of-Change Record.

SP3 Line Twenty seven - The Velocity and Clock Rate-of-Change Correlation Record (See example 2)

Columns 1-2	Symbols	EV	A2
Columns 3-4	Unused		2 blanks
Columns 5-8	xvel-sdev	22	I4
	(10**-4 mm/sec)		
Column 9	Unused		blank
Columns 10-13	yvel-sdev	22	I4
	(10**-4 mm/sec)		
Column 14	Unused		blank
Columns 15-18	zvel-sdev	22	I4
	(10**-4 mm/sec)		
Column 19	Unused		blank
Columns 20-26	clkrate-sdev	111	I7
	(10**-4 psec/sec)		
Column 27	Unused		blank
Columns 28-35	xy-correlation	1234567	I8
Column 36	Unused		blank
Columns 37-44	xz-correlation	1234567	I8
Column 45	Unused		blank
Columns 46-53	xc-correlation	1234567	I8
Column 54	Unused		blank
Columns 55-62	yz-correlation	1234567	I8
Column 63	Unused		blank
Columns 64-71	yc-correlation	1234567	I8
Column 72	Unused		blank
Columns 73-80	zc-correlation	1234567	I8

If no Velocity and Clock Rate-of-Change Records or Correlation Records are present, the last line in the file can be computed as follows:

SP3 Line 22+NUMEPS*(NUMSATS+1)+1 (i.e., The Last Line)

Columns 1-3	End of File	EOF	A3
-------------	-------------	-----	----

Discussion of the SP3-c Format

On line one, character two is the format version identification character. This third SP3 version has been designated version 'c'. Subsequent versions will use lower case letters in alphabetical order. The first line comprises the Gregorian date and time of day of the first epoch of the orbit, the number of epochs in the ephemeris file (up to 10 million), the data used descriptor, the coordinate system used descriptor, the orbit type descriptor, and the agency descriptor. The data used descriptor was included for ease in distinguishing between multiple orbital solutions from a single organization. This will have primary use for the agency generating the orbit. A possible convention is given below; this is not considered final and suggestions are welcome.

```

u  -- undifferenced carrier phase
du -- change in u with time
s  -- 2-receiver/1-satellite carrier phase
ds -- change on s with time
d  -- 2-receiver/2-satellite carrier phase
dd -- change in d with time
U  -- undifferenced code phase
dU -- change in U with time
S  -- 2-receiver/1-satellite code phase
dS -- change in S with time
D  -- 2-receiver/2-satellite code phase
dD -- change in D with time
+  -- type separator

```

Combinations such as "u+U" seem reasonable. If the measurements used were complex combinations of standard types, then one could use "mixed" where mixed could be explained on the comment lines. In examples 1 and 2, the file is a combination of orbits from several agencies and so the data used is designated as 'ORBIT'.

Orbit type is described by a three character descriptor. At this time only four have been defined: FIT (fitted), EXT (extrapolated or predicted), BCT (broadcast), and HLM (fitted after applying a Helmert transformation). Naturally, others are possible. The computing agency descriptor allows four characters (e.g. NGS, IGS, etc.).

The second line has: the GPS week; the seconds of the GPS Week elapsed at the start of the orbit (0.0 <= seconds of week < 604800.0); the epoch interval (0.0 < epoch interval < 100000.0) in seconds; the modified Julian Day Start (where 44244 represents GPS zero time -- January 6, 1980); and fractional part of the day (0.0 <= fractional < 1.0) at the start of the orbit.

The third line to the seventh lines indicate the number of satellites followed by their respective identifiers. The identifiers must use consecutive slots and continue on lines 4-7, if required. The value 0 should only appear after all the identifiers are listed. Satellite identifiers may be listed in any order. However, for ease in reviewing satellites included in the orbit file it is recommended that alphabetical/numerical order be used. Each identifier will consist of a letter followed by a 2-digit integer between 01 and 99. For example, "Gnn" for GPS satellites, "Rnn" for GLONASS satellites, "Lnn" for Low-Earth Orbiting (LEO) satellites, "Enn" for Galileo satellites, "Cnn" for COMPASS satellites, and "Jnn" for QZSS satellites. For QZSS the nn=PRN-192 rule is applied, for example QZS-1 (PRN=193) is expressed by "J01". Other letters will be allowed for other types of satellites. Lower numbered satellites must always have a preceding zero (e.g., "G09" not "G 9"). The letter, which represents the Satellite System Indicator, must always be present (i.e., "09" is no longer a valid satellite identifier). This is a

sp3c

significant change from SP3-a and needs to be noted when software is updated to read the new SP3-c format. A list of identifiers created for LEO satellites can be viewed at http://cddis.gsfc.nasa.gov/sp3c_satlist.html .

The eighth line to the twelfth lines have the orbit accuracy exponents. The value 0 is interpreted as accuracy unknown. A satellite's accuracy exponent appears in the same slot on lines 8-12 as the identifier on lines 3-7. The accuracy is computed from the exponent as in the following example. If the accuracy exponent is 13, the accuracy is 2^{**13} mm or ~ 8 m. The quoted orbital error should represent one standard deviation and be based on the orbital error in the entire file for the respective satellite. This may lead to some distortion when orbit files are joined together, or when a file contains both observed and predicted data.

On the thirteenth line, columns 4-5 hold the File Type descriptor. This is a single character left-justified in the two-character field. The currently defined values are: "G " for GPS only files, "M " for mixed files, "R " for GLONASS only files, "L " for LEO only files, "E " for Galileo only files, "C " for COMPASS only files, and "J " for QZSS only files. No default values are implied; either "G ", "M ", "R ", "L ", "E ", "C ", or "J " is required. On this same line, columns 10-12 hold the Time System Indicator. In order to remove any ambiguity with respect to which time system is being used in mixed files, this field specifies the time system used in each SP3-c file: use "GPS" to identify GPS Time, "GLO" to identify the GLONASS UTC time system, "GAL" to identify Galileo system time, "TAI" to identify International Atomic Time, "UTC" to identify Coordinated Universal Time, or "QZS" to identify QZSS Time. No default value is implied; either "GPS", "GLO", "GAL", "TAI", "UTC", or "QZS" must be specified.

On Line fifteen, columns 4-13 hold the floating-point base number used for computing the standard deviations for the components of the satellite position and velocity. Instead of using $2^{*}mn$ as is done in lines 8-12 in the header, better resolution can be attained using a number like $1.25^{*}nn$. The units for position and velocity are mm and 10^{*-4} mm/sec, respectively. Likewise, columns 15-26 hold the floating-point base number for computing the standard deviations for the clock correction and the rate-of-change of the clock correction. Again, instead of using $2^{*}nnn$, one might use a number like $1.025^{*}nnn$. The units for the clock correction and the rate-of-change of the clock correction are picosec and 10^{*-4} picosec/sec, respectively.

Lines 13-18 have been designed so that additional parameters may be added to the SP3 format.

Lines 19-22 are free form comments (comments go in columns 4-60).

Line 23 is the Epoch Header Record, showing the epoch date and time.

Line 24 is the Position and Clock Record; the first character is always 'P'. The positional values are in kilometers and are precise to 1 mm. A precision of 0.5 mm can be accommodated if rounding is used, i.e., the value shown is never more than 0.5 mm from the computed value. The clock values are in microseconds and are precise to 1 picosecond. Bad or absent positional values are to be set to 0.000000. Bad or absent clock values are to be set to 999999.999999. The six integer nines are required, whereas the fractional part nines are optional. Columns 62-69 hold the two digit exponents which represent the standard deviations of the satellite coordinates in units of millimeters. For example, if the base floating point number from line fifteen is 1.25, and the two-digit exponent for the X-coordinate is 18, then the standard deviation of the X-coordinate is $1.25^{*}18 = 55.5112$ or approximately 56 mm. In a similar manner, columns 71-73 hold a three-digit exponent representing the standard deviation for the clock correction in units of picoseconds. As an example, if the base

sp3c

floating point number from line fifteen is 1.025, and the three-digit exponent for the clock correction is 219, then the standard deviation of the clock correction is $1.025 \times 10^{219} = 223.1138$ or approximately 223 picoseconds. An exponent value of 99 or 999 would mean that a standard deviation was too large to represent. If a standard deviation is unknown, its field is left blank. Column 75 is the Clock Event Flag (either 'E' or blank). An 'E' flag is used to denote a discontinuity in the satellite clock correction (this might be caused by a clock swap on the satellite). The discontinuity is understood to have occurred sometime between the previous epoch and current epoch, or at the current epoch. A blank means either no event occurred, or it is unknown whether any event occurred. Column 76 is the Clock Correction Prediction Flag (either 'P' or blank). A 'P' flag indicates that the satellite clock correction at this epoch is predicted. A blank means that the clock correction is observed. Column 79 is the orbit Maneuver Flag (either 'M' or blank). An 'M' flag indicates that sometime between the previous epoch and the current epoch, or at the current epoch, an orbit maneuver took place for this satellite. As an example, if a certain maneuver lasted 50 minutes (a satellite changing orbital planes) then these M-flags could conceivably appear at five separate 15-minute orbit epochs. If the maneuver started at 11h 14m and lasted to 12h 04m, M-flags would appear for the epochs 11:15, 11:30, 11:45, 12:00 and 12:15. A maneuver is loosely defined as any planned or humanly-detectable thruster firing that changes the orbit of a satellite. A blank means either no maneuver occurred, or it is unknown whether any maneuver occurred. Column 80 is the Orbit Prediction Flag (either 'P' or blank). A 'P' flag indicates that the satellite position at this epoch is predicted. A blank means that the satellite position is observed. Since not all of the fields in columns 61 through 80 will be used at every epoch, not every Position and Clock Record will be required to contain 80 columns; missing columns should be interpreted as blanks. Any program reading an SP3-c file must be prepared to deal with short records (either by padding with blanks, or by some other method).

Line 25 (in example 2) is the optional Position and Clock Correlation Record. This record type always begins with the characters 'EP'. Columns 5-18 give the standard deviations for the X,Y,Z satellite coordinates in units of mm. The standard deviations in this record are given to greater resolution than the approximate values given in the Position and Clock Record. A value of 9999 would mean that a standard deviation was too large to be represented. If a standard deviation is unknown, its field is left blank. Columns 20-26 give the standard deviation of the clock correction in units of picoseconds. A value of 9999999 would mean that the standard deviation was too large to be represented. Columns 28-80 are used to store the correlation coefficients for xy, xz, xc, yz, yc, and zc. Each 8-digit integer would be divided by 10,000,000 to produce a correlation coefficient between -0.9999999 and +0.9999999. If some of the correlation coefficients are omitted, a Position and Clock Correlation Record may contain less than 80 columns.

Line 26 (in example 2) is the optional Velocity and Clock Rate-of-Change Record. This type of record always begins with the character 'V'. When the position/velocity mode flag is set to 'V' in line one, then each Position and Clock Record for a satellite will be followed by a corresponding Velocity and Clock Rate-of-Change Record (although in some cases there may be a Position and Clock Correlation Record in between the two). The satellite velocity components are given in columns 5-46 in units of decimeters/second and have a precision of 10^{-4} millimeters/second. Columns 47-60 give the rate-of-change of the clock correction in units of 10^{-4} microseconds/second. The precision of this parameter is 10^{-16} seconds/second. Bad or absent velocity values are to be set to 0.000000. Bad or absent clock rate-of-change values are to be set to 999999.999999. The six integer nines are required, whereas the fractional part nines are optional. In a manner similar to the Position and Clock Record,

sp3c

columns 62-69 hold two-digit exponents for representing the standard deviation of the X-, Y-, Z-velocities (e.g., $1.25 \times 10^{14} = 22.7374$ or approximately 0.0022 mm/sec). Columns 71-73 hold a three-digit exponent for representing the standard deviation of the clock correction rate-of-change (e.g., $1.025 \times 10^{191} = 111.7528$ or approximately 0.0112 psec/sec). A value of 99 or 999 would mean that a standard deviation was too large to represent. If a standard deviation is unknown, its field is left blank. If one or more fields in columns 61 through 73 are omitted, a Velocity and Clock Rate-of-Change Record may contain less than 73 columns.

Line 27 (in example 2) is the optional Velocity and Clock Rate-of-Change Correlation Record. This type of line always begins with the characters 'EV'. Columns 5-18 give the standard deviations for the X-, Y-, Z-velocities in units of 10^{-4} millimeters/second. The standard deviations of the velocity components are given to greater resolution than the approximate values given in the Velocity and Clock Rate-of-Change Record. A value of 9999 would mean that a velocity standard deviation was too large to be represented. Columns 20-26 give the standard deviation of the clock correction rate-of-change in units of 10^{-4} psec/sec. A value of 9999999 would mean that the clock correction rate-of-change was too large to be represented. If a standard deviation is unknown, its field is left blank. Columns 28-80 are used to store the correlation coefficients between the velocity components and the clock correction rate-of-change (xy, xz, xc, yz, yc, and zc). Each 8-digit integer would be divided by 10,000,000 to produce a correlation coefficient between -0.9999999 and +0.9999999. If some of the correlation coefficients are omitted, a Velocity and Clock Rate-of-Change Correlation Record may contain less than 80 columns.

FINAL NOTE: Any software which reads SP3-c files must be prepared to read the 'EP' and 'EV' correlation records if they are present. If the person or agency using the file decides that the correlation information (and the more accurate standard deviations) are not needed, then these 'EP' and 'EV' records might be stripped out to save space, or simply ignored and skipped over. There may be only a few EP and/or EV records placed in an SP3-c file, i.e., it is not necessary to have EP and/or EV records for every satellite at every epoch (as shown in Example 2 below). The only rule is: since no satellite IDs are given in the optional EP and EV records, they must immediately follow their corresponding P or V record for that satellite. The satellite order of the P, EP, V, and EV records (or subset of these) must be the same as the order of the satellite IDs in lines 3 through 7 in the header. Thus the order and the total number of satellites at each epoch must always be the same. This serves as an integrity check on the file -- i.e., satellites must be designated as "bad" or "absent" by intentionally setting their position (and velocity) values equal to zero. There should never be any satellite's Position or Velocity records left out at an epoch. Since not all SP3-c records will contain their maximum number of columns, missing columns should be interpreted as blanks. Any program reading an SP3-c file must be prepared to deal with short records (either by padding with blanks, or by some other method).

Example 1. SP3-c file with Position and Clock Record used at each epoch.

```
#cP2001 8 8 0 0 0.00000000 192 ORBIT IGS97 HLM IGS
## 1126 259200.00000000 900.00000000 52129 0.00000000000000
+ 26 G01G02G03G04G05G06G07G08G09G10G11G13G14G17G18G20G21
+ G23G24G25G26G27G28G29G30G31 0 0 0 0 0 0 0 0
+ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
+ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
++ 7 8 7 8 6 7 7 7 7 7 7 7 8 8 7 9
++ 9 8 6 8 7 7 6 7 7 0 0 0 0 0 0 0
```

```

                                sp3c
++      0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
++      0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
++      0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
%c G   cc GPS ccc cccc cccc cccc cccc ccccc ccccc ccccc ccccc
%c cc cc ccc ccc cccc cccc cccc cccc ccccc ccccc ccccc ccccc
%f 1.2500000 1.025000000 0.00000000000 0.00000000000000000000
%f 0.00000000 0.0000000000 0.000000000000 0.00000000000000000000
%i 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
%i 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
/* ULTRA ORBIT COMBINATION FROM WEIGHTED AVERAGE OF:
/* cou esu gfu jpu siu usu
/* REFERENCED TO cou CLOCK AND TO WEIGHTED MEAN POLE:
/* CLK ANT Z-OFFSET (M): II/IIA 1.023; IIR 0.000
* 2001 8 8 0 0 0.00000000
PG01 -11044.805800 -10475.672350 21929.418200 189.163300 18 18 18 219
PG02 -12593.593500 10170.327650 -20354.534400 -55.976000 18 18 18 219 M
PG03 9335.606450 -21952.990750 -11624.350150 54.756700 18 18 18 219
PG04 -16148.976900 8606.630600 19407.845050 617.997800 18 18 18 219
PG05 13454.631450 20956.333700 9376.994100 308.956400 18 18 18 219
PG06 18821.523100 1138.155450 18958.305500 -2.406900 18 18 18 219
.
.
.
* 2001 8 9 23 45 0.00000000
PG01 -11044.805800 -10475.672350 21929.418200 189.163300 18 18 18 219 P P
PG02 -12593.593500 10170.327650 -20354.534400 -55.976000 18 18 18 219 P P
PG03 9335.606450 -21952.990750 -11624.350150 54.756700 18 18 18 219 P P
PG04 -16148.976900 8606.630600 19407.845050 617.997800 18 18 18 219 EP P
.
.
.
PG30 -20393.814200 16198.067550 -4138.151700 428.892900 18 18 18 219 P P
PG31 -23592.378250 1395.049800 -12524.037100 461.972900 18 18 18 219 P P
EOF

```

Example 2. SP3-c file with all record types (P, EP, V, EV) used at each epoch.

```

#cV2001 8 8 0 0 0.00000000 192 ORBIT IGS97 HLM IGS
## 1126 259200.00000000 900.00000000 52129 0.0000000000000000
+ 26 G01G02G03G04G05G06G07G08G09G10G11G13G14G17G18G20G21
+ G23G24G25G26G27G28G29G30G31 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
+ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
+ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
+ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
++ 7 8 7 8 6 7 7 7 7 7 7 7 7 8 8 7 9
++ 9 8 6 8 7 7 6 7 7 0 0 0 0 0 0 0 0 0 0 0 0
++ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
++ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
++ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
%c G   cc GPS ccc cccc cccc cccc cccc ccccc ccccc ccccc ccccc
%c cc cc ccc ccc cccc cccc cccc cccc ccccc ccccc ccccc ccccc
%f 1.2500000 1.025000000 0.00000000000 0.00000000000000000000
%f 0.00000000 0.0000000000 0.000000000000 0.00000000000000000000
%i 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
%i 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
/* ULTRA ORBIT COMBINATION FROM WEIGHTED AVERAGE OF:
/* cou esu gfu jpu siu usu
/* REFERENCED TO cou CLOCK AND TO WEIGHTED MEAN POLE:
/* CLK ANT Z-OFFSET (M): II/IIA 1.023; IIR 0.000
* 2001 8 8 0 0 0.00000000

```

```

                                sp3c
PG01 -11044.805800 -10475.672350 21929.418200 189.163300 18 18 18 219
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG01 20298.880364 -18462.044804 1381.387685 -4.534317 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
PG02 -12593.593500 10170.327650 -20354.534400 -55.976000 18 18 18 219 M
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG02 -9481.923808 -25832.652567 -7277.160056 8.801258 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
PG03 9335.606450 -21952.990750 -11624.350150 54.756700 18 18 18 219
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG03 12497.392894 -8482.260298 26230.348459 5.620682 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
PG04 -16148.976900 8606.630600 19407.845050 617.997800 18 18 18 219
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG04 -22859.768469 -8524.538983 -15063.229095 -3.292980 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
PG05 13454.631450 20956.333700 9376.994100 308.956400 18 18 18 219
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG05 392.255680 12367.086937 -27955.768747 -13.600595 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
.
.
* 2001 8 9 23 45 0.00000000
PG01 -11044.805800 -10475.672350 21929.418200 189.163300 18 18 18 219 P P
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG01 20298.880364 -18462.044804 1381.387685 -4.534317 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
PG02 -12593.593500 10170.327650 -20354.534400 -55.976000 18 18 18 219 P P
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG02 -9481.923808 -25832.652567 -7277.160056 8.801258 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
.
.
PG30 -23592.378250 1395.049800 -12524.037100 461.972900 18 18 18 219 P P
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG30 -13996.847785 -6945.665482 25908.199568 0.364488 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
PG31 17353.533200 15151.105700 -13851.534050 -1.841700 18 18 18 219 P P
EP 55 55 55 222 1234567 -1234567 5999999 -30 21 -1230000
VG31 -16984.306646 -2424.913336 -23969.277677 -14.371692 14 14 14 191
EV 22 22 22 111 1234567 1234567 1234567 1234567 1234567 1234567
EOF

```

ACKNOWLEDGMENTS

The idea for using floating-point base numbers (1.25**nn and 1.025**nnn, rather than 2**nn) to improve the resolution of the standard deviations was suggested by Benjamin Remondi. The author would also like to thank the several members of the IGS community who offered comments and suggestions on the design of the SP3-c format: Henno Boomkamp, Gerd Gendt, Werner Gurtner, Urs Hugentobler, Jan Kouba, Stephen Malys, Tomas Martin Mur, Jim Ray, Ignacio Romero, Markus Rothacher, Mark Schenewerk, Victor Slabinski, Tim Springer, Everett Swift, and Robert Weber.

REFERENCES

sp3c

1. Remondi, B. W. 1985: Distribution of Global Positioning System Ephemerides by the National Geodetic Survey, Presented at the First Conference on Civil Applications of GPS - Institute of Navigation, September 12, 1985, 8 pp.
2. Remondi, B. W. 1989: Extending the National Geodetic Survey Geodetic Orbit Formats, NOAA Technical Report 133 NGS 46, 85 pp.
3. Remondi, B. W., 1991: NGS Second Generation ASCII and Binary Orbit Formats and Associated Interpolated Studies, Proceedings of the Twentieth General Assembly, International Union of Geodesy and Geophysics, Vienna, Austria, August 11-24, 1991, 28 pp.
4. Gurtner, W., 2000: RINEX: The Receiver-Independent Exchange Format, GPS World, Volume 5, Number 7, 48-52. Also available from:
<ftp://igscb.jpl.nasa.gov/igscb/data/format/rinex210.txt>
5. Hilla, S., 2002: Extending the Standard Product 3 (SP3) Orbit Format, Proceedings of the International GPS Service Network, Data, and Analysis Center Workshop, Ottawa, Canada, April 8-11, 2002.
6. Spofford, P. R. and Remondi, B. W., 1994: The National Geodetic Survey Standard GPS Format SP3. (SP3-a format) available from the IGS website:
http://igscb.jpl.nasa.gov/igscb/data/format/sp3_docu.txt
7. The NIMA SP3 format can be viewed at
<http://164.214.2.59/GandG/sathtml/sp3format.html>
8. The IGEX98 SP3-b format [IGEX Mail-0042, SP3 Modifications (corrigenda)] can be viewed at <http://igscb.jpl.nasa.gov/mail/igexmail/1998/msg00041.html>
9. A list of identifiers for Low-Earth Orbiting satellites can be viewed at http://cdis.gsfc.nasa.gov/sp3c_satlist.html