

Dependence Analysis

Monday, November 17, 14

Motivating question

- Can the loops on the right be run in parallel?
- i.e., can different processors run different iterations in parallel?
- What needs to be true for a loop to be parallelizable?
- Iterations cannot interfere with each other
- No *dependence* between iterations

```
for (i = 1; i < N; i++) {
    a[i] = b[i];
    c[i] = a[i - 1];
}
```


```
for (i = 1; i < N; i++) {
    a[i] = b[i];
    c[i] = a[i] + b[i - 1];
}
```

Monday, November 17, 14

Dependences

- A *flow dependence* occurs when one iteration writes a location that a *later* iteration reads

```
for (i = 1; i < N; i++) {
    a[i] = b[i];
    c[i] = a[i - 1];
}
```



Monday, November 17, 14

Running a loop in parallel

- If there is a dependence in a loop, we cannot guarantee that the loop will run correctly in parallel
- What if the iterations run out of order?
 - Might read from a location before the correct value was written to it
- What if the iterations do not run in lock-step?
 - Same problem!

Monday, November 17, 14

Other kinds of dependence

- Anti dependence* – When an iteration *reads* a location that a later iteration *writes* (why is this a problem?)

```
for (i = 1; i < N; i++) {
    a[i - 1] = b[i];
    c[i] = a[i];
}
```


- Output dependence* – When an iteration *writes* a location that a later iteration *writes* (why is this a problem?)

```
for (i = 1; i < N; i++) {
    a[i] = b[i];
    a[i + 1] = c[i];
}
```

Monday, November 17, 14

Data dependence concepts

- Dependence *source* is the earlier statement (the statement at the tail of the dependence arrow)
- Dependence *sink* is the later statement (the statement at the head of the dependence arrow)



- Dependences can only go forward in time: always from an earlier iteration to a later iteration.

Monday, November 17, 14

Using dependences

- If there are no dependences, we can parallelize a loop
 - None of the iterations interfere with each other
- Can also use dependence information to drive other optimizations
 - Loop interchange
 - Loop fusion
 - (We will discuss these later)
- Two questions:
 - How do we represent dependences in loops?
 - How do we determine if there are dependences?

Monday, November 17, 14

Representing dependences

- Focus on flow dependences for now
- Dependences in straight line code are easy to represent:
 - One statement writes a location (variable, array location, etc.) and another reads that same location
 - Can figure this out using reaching definitions
- What do we do about loops?
- We often care about dependences between the same statement in different iterations of the loop!

```
for (i = 1; i < N; i++) {
    a[i + 1] = a[i] + 2
}
```

Monday, November 17, 14

Iteration space graphs

- Represent each *dynamic* instance of a loop as a point in a graph
- Draw arrows from one point to another to represent dependences

```
for (i = 0; i < N; i++) {
    a[i + 2] = a[i]
}
```

Monday, November 17, 14

Iteration space graphs

- Represent each *dynamic* instance of a loop as a point in a graph
- Draw arrows from one point to another to represent dependences

```
for (i = 0; i < N; i++) {
    a[i + 2] = a[i]
}
```

- Step 1: Create nodes, I for each iteration
 - Note: not I for each array location!




Monday, November 17, 14

Iteration space graphs

- Represent each *dynamic* instance of a loop as a point in a graph
- Draw arrows from one point to another to represent dependences

```
for (i = 0; i < N; i++) {
    a[i + 2] = a[i]
}
```

- Step 2: Determine which array elements are read and written in each iteration




Monday, November 17, 14

Iteration space graphs

- Represent each *dynamic* instance of a loop as a point in a graph
- Draw arrows from one point to another to represent dependences

```
for (i = 0; i < N; i++) {
    a[i + 2] = a[i]
}
```

- Step 3: Draw arrows to represent dependences




Monday, November 17, 14

2-D iteration space graphs

- Can do the same thing for doubly-nested loops
- 2 loop counters

```
for (i = 0; i < N; i++)
  for (j = 0; j < N; j++)
    a[i+1][j-2] = a[i][j] + 1
```



Monday, November 17, 14

Iteration space graphs

- Can also represent output and anti dependences
 - Use different kinds of arrows for clarity. E.g.
 - \rightarrow for output
 - \dashrightarrow for anti
- Crucial problem: Iteration space graphs are potentially infinite representations!
- Can we represent dependences in a more compact way?

Monday, November 17, 14


Distance and direction vectors

- Compiler researchers have devised *compressed* representations of dependences
 - Capture the same dependences as an iteration space graph
 - May lose *precision* (show more dependences than the loop actually has)
- Two types
 - Distance vectors: captures the “shape” of dependences, but not the particular source and sink
 - Direction vectors: captures the “direction” of dependences, but not the particular shape

Monday, November 17, 14

Distance vector

- Represent each dependence arrow in an iteration space graph as a vector
- Captures the “shape” of the dependence, but loses where the dependence originates




- Distance vector for this iteration space: (2)
- Each dependence is 2 iterations forward

Monday, November 17, 14

2-D distance vectors

- Distance vector for this graph:
 - (1, -2)
- +1 in the i direction, -2 in the j direction
- Crucial point about distance vectors: they are always “positive”
 - First non-zero entry has to be positive
- Dependences can’t go backwards in time




Monday, November 17, 14

More complex example

- Can have multiple distance vectors

```
for (i = 0; i < N; i++)
  for (j = 0; j < N; j++)
    a[i+1][j-2] = a[i][j] + a[i-1][j-2]
```




Monday, November 17, 14

More complex example

- Can have multiple distance vectors

```
for (i = 0; i < N; i++)
  for (j = 0; j < N; j++)
    a[i+1][j-2] = a[i][j] +
      a[i-1][j-2]
```

- Distance vectors
 - (1, -2)
 - (2, 0)
- Important point: order of vectors depends on order of loops, not use in arrays




Monday, November 17, 14

Problems with distance vectors

- The preceding examples show how distance vectors can summarize all the dependences in a loop nest using just a small number of distance vectors
- Can't always summarize as easily
- Running example:


```
for (i = 0; i < N; i++)
  a[2*i] = a[i];
```



Monday, November 17, 14

Loss of precision


- What are the distance vectors for this code?
 - (1), (2), (3), (4) ...
- Note: we have information about the length of each vector, but not about the source of each vector
- What happens if we try to reconstruct the iteration space graph?



Monday, November 17, 14

Loss of precision

- What are the distance vectors for this code?
 - (1), (2), (3), (4) ...
- Note: we have information about the length of each vector, but not about the source of each vector
- What happens if we try to reconstruct the iteration space graph?



Monday, November 17, 14

Direction vectors

- The whole point of distance vectors is that we want to be able to succinctly capture the dependences in a loop nest
 - But in the previous example, not only did we add a lot of extra information, we still had an infinite number of distance vectors
- Idea: summarize distance vectors, and save only the *direction* the dependence was in
 - (2, -1) → (+, -)
 - (0, 1) → (0, +)
 - (0, -2) → (0, -)
 - (can't happen; dependences have to be positive)
- Notation: sometimes use '<' and '>' instead of '+' and '-'

Monday, November 17, 14

Why use direction vectors?

- Direction vectors lose a lot of information, but do capture some useful information
 - Whether there is a dependence (anything other than a '0' means there is a dependence)
 - Which dimension and direction the dependence is in
- Many times, the only information we need to determine if an optimization is legal is captured by direction vectors
 - Loop parallelization
 - Loop interchange

Monday, November 17, 14

Loop parallelization

Monday, November 17, 14

Loop-carried dependence

- The key concept for parallelization is the *loop carried dependence*
- A dependence that crosses loop iterations
- If there is a loop carried dependence, then that loop *cannot* be parallelized
- Some iterations of the loop depend on other iterations of the same loop

Monday, November 17, 14

Examples

```
for (i = 0; i < N; i++)
    a[2*i] = a[i];
```

Later iterations of i loop
depend on earlier iterations

```
for (i = 0; i < N; i++)
    for (j = 0; j < N; j++)
        a[i+1][j-2] = a[i][j] + 1
```

Later iterations of both i and
j loops depend on earlier iterations


Monday, November 17, 14

Some subtleties

- Dependences might only be carried over one loop!

```
for (i = 0; i < N; i++)
    for (j = 0; j < N; j++)
        a[i][j+1] = a[i][j] + 1
```

- Can parallelize i loop, but not j loop




Monday, November 17, 14

Some subtleties

- Dependences might only be carried over one loop!

```
for (i = 0; i < N; i++)
    for (j = 0; j < N; j++)
        a[i+1][j] = a[i-1][j] + 1
```

- Can parallelize j loop, but not i loop



Monday, November 17, 14

Direction vectors

- So how do direction vectors help?
- If there is a non-zero entry for a loop dimension, that means that there is a loop carried dependence over that dimension
- If an entry is zero, then that loop can be parallelized!
- May be able to parallelize inner loop even if entry is not zero, but you have to carefully structure parallel execution

Monday, November 17, 14

Improving parallelism

- Important point: any dependence can prevent parallelization
- Anti and output dependences are important, not just flow dependences
- But anti and output dependences can be removed by using more storage
 - Like register renaming in out-of-order processors
- In principle, all anti and output dependences can be removed, but this is difficult
- Key question: when are there flow dependences?

```
for (i = 0; i < N; i++)
    a[i] = a[i + 1] + 1
    ↓
for (i = 0; i < N; i++)
    aa[i] = a[i + 1] + 1
```

Monday, November 17, 14

Data Dependence Tests

Monday, November 17, 14

Problem formulation

- Given the loop nest:


```
for (i = 0; i < N; i++)
    a[f(i)] = ...
    ... = a[g(i)]
```
- A dependence exists if there exist an integer i and an i' such that:
 - $f(i) = g(i')$
 - $0 \leq i, i' < N$
 - If $i < i'$, write happens before read (flow dependence)
 - If $i > i'$, write happens after read (anti dependence)

Monday, November 17, 14

Loop normalization

- Loops that skip iterations can always be *normalized* to loops that don't, so we only need to consider loops that have unit strides
- Note: this is essentially of the reverse of linear test replacement

```
for (i = L; i < U; i += S)
    ... a[i] ...
    ↓
for (i = 0; i < (U - L)/S; i += 1)
    ... a[S*i + L] ...
```

Monday, November 17, 14

Diophantine equations

- An equation whose coefficients and solutions are all integers is called a *Diophantine equation*
- Our question:

$$f(i) = a*i + b \quad g(i) = c*i + d$$

Does $f(i) = g(i')$ have a solution?
- $f(i) = g(i') \Rightarrow ai + b = ci' + d \Rightarrow a_1*i + a_2*i' = a_3$

Monday, November 17, 14

Solutions to Diophantine eqns

- An equation $a_1*i + a_2*i' = a_3$ has a solution iff $\gcd(a_1, a_2)$ evenly divides a_3
- Examples
 - $15*i + 6*j - 9*k = 12$ has a solution ($\gcd = 3$)
 - $2*i + 7*j = 3$ has a solution ($\gcd = 1$)
 - $9*i + 6*j = 10$ has no solution ($\gcd = 3$)

Monday, November 17, 14

Why does this work?

- Suppose g is the $\text{gcd}(a, b)$ in $a*i + b*j = c$
- Can rewrite equation as
$$g*(a'*i + b'*j) = c$$
$$a' * i + b' * j = c/g$$
- a' and b' are integers, and relatively prime ($\text{gcd} = 1$) so by choosing i and j correctly, can produce *any* integer, but *only* integers
- Equation has a solution provided c/g is an integer

Monday, November 17, 14

Finding the GCD

- Finding GCD with Euclid's algorithm
 - Repeat
$$a = a \bmod b$$
swap a and b until b is 0 (resulting a is the gcd)
- Why? If g divides a and b , then g divides $a \bmod b$

```
gcd(27, 12): a = 27, b = 15
a = 27 mod 15 = 12
a = 15 mod 12 = 3
a = 12 mod 3 = 0
gcd = 3
```

Monday, November 17, 14

Downsides to GCD test

- If $f(i) = g(i')$ fails the GCD test, then there is no i, i' that can produce a dependence \rightarrow loop has no dependences
- If $f(i) = g(i')$, there *might* be a dependence, but might not
 - i and i' that satisfy equation might fall outside bounds
 - Loop may be parallelizable, but cannot tell
- Unfortunately, most loops have $\text{gcd}(a, b) = 1$, which divides everything
- Other optimizations (loop interchange) can tolerate dependences in certain situations

Monday, November 17, 14

Other dependence tests

- GCD test: doesn't account for loop bounds, does not provide useful information in many cases
- Banerjee test (Utpal Banerjee): accurate test, takes directions and loop bounds into account
- Omega test (William Pugh): even more accurate test, precise but can be very slow
- Range test (Blume and Eigenmann): works for non-linear subscripts
- Compilers tend to perform simple tests and only perform more complex tests if they cannot prove non-existence of dependence

Monday, November 17, 14

Other loop optimizations

- We've seen this one before
- Interchange doubly-nested loop to
 - Improve locality
 - Improve parallelism
 - Move parallel loop to outer loop (coarse grained parallelism)

Monday, November 17, 14

Monday, November 17, 14

Loop interchange

Loop interchange legality

- We noted that loop interchange is not always legal, because it reorders a computation
- Can we use dependences to determine legality?


Monday, November 17, 14

Loop interchange dependences

- Consider interchanging the following loop, with the dependence graph to the right:

```
for (i = 0; i < N; i++)
  for (j = 0; j < N; j++)
    a[i+1][j+2] = a[i][j] + 1
```

- Distance vector (1, 2)
- Direction vector (+, +)




Monday, November 17, 14

Loop interchange dependences

- Consider interchanging the following loop, with the dependence graph to the right:

```
for (j = 0; j < N; j++)
  for (i = 0; i < N; i++)
    a[i+1][j+2] = a[i][j] + 1
```

- Distance vector (2, 1)
- Direction vector (+, +)
- Distance vector gets swapped!



Monday, November 17, 14

Loop interchange legality


- Interchanging two loops swaps the order of their entries in distance/direction vectors
- (0, +) → (+, 0)
- (+, 0) → (0, +)
- But remember, we can't have backwards dependences
- (+, -) → (-, +)
- Illegal dependence → Loop interchange not legal!

Monday, November 17, 14

Loop interchange dependences

- Example of illegal interchange:

```
for (i = 0; i < N; i++)
  for (j = 0; j < N; j++)
    a[i+1][j-2] = a[i][j] + 1
```




Monday, November 17, 14

Loop interchange dependences

- Example of illegal interchange:

```
for (j = 0; j < N; j++)
  for (i = 0; i < N; i++)
    a[i+1][j-2] = a[i][j] + 1
```

- Flow dependences turned into anti-dependences
- Result of computation will change!



Monday, November 17, 14

Loop fusion/distribution

- Loop fusion: combining two loops into a single loop
 - Improves locality, parallelism
- Loop distribution: splitting a single loop into two loops
 - Can increase parallelism (turn a non-parallelizable loop into a parallelizable loop)
- Legal as long as optimization maintains dependences
 - Every dependence in the original loop should have a dependence in the optimized loop
 - Optimized loop should not introduce new dependences

Monday, November 17, 14

Fusion/distribution example

- Code 1:

```
for (i = 0; i < N; i++)  
  a[i - 1] = b[i]
```



```
for (j = 0; j < N; j++)  
  c[j] = a[j]
```
- Code 2:

```
for (i = 0; i < N; i++)  
  a[i - 1] = b[i]  
  c[i] = a[i]
```
- Dependence graph
 - All red iterations finish before blue iterations → flow dependence
- Dependence graph
 - i iterations finish before i+1 iterations → flow dependence now an anti dependence!

Monday, November 17, 14

Fusion/distribution utility

```
for (i = 0; i < N; i++)  
  a[i] = a[i - 1]  → Fusion → for (i = 0; i < N; i++)  
                                a[i] = a[i - 1]  
for (j = 0; j < N; j++)  ← Distribution ← b[j] = a[j]
```

- Fusion and distribution both legal
- Right code has better locality, but cannot be parallelized due to loop carried dependences
- Left code has worse locality, but blue loop can be parallelized

Monday, November 17, 14